



BP337N3-i3K

Modular Self-Checkout Kiosk



Modular Design in Self-Checkout Innovation

Smart Retail Solutions

Elevate Space with Adaptable Placement

Smart Mounting Solutions for Effortless Add-Ons



intel Intel® Core i3-N305
CORE 8GB DDR4
 128GB SSD


Powerful Hardware Platforms

Windows **Linux**

Supports Multiple OS



Mounting Holes for Handheld Scanner



Mounting Holes for Payment Device



Pedestal Stand Option for Smart Bagging Solutions

Specifications		Model: BP337N3-i3K
System	Motherboard	G35
	Processor	Intel® Core i3-N305, 6M Cache, up to 3.80 GHz
	Memory	1 x DDR4 upto 8GB
	Storage	128GB SSD (M.2)
Display	Size and Resolution	15.6" 1920x1080
	Touch Screen	True-Flat PCAP multi-touch
I/O Ports	USB Type-A	2x USB3.0, 4x USB2.0
	USB Type-C	1x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A)
	FeDP	2x Flytech proprietary miniDP (1 for the main display, 1 for the 2nd display)
	Serial Port	3x RJ48 (standard RS232) (default 0V; 5V.12V)
	LAN	1xRJ45
	Cash Drawer	1xRJ11
	DC Jack	1x4PIN (with latch)
	Optional I/O	Powered USB
Audio	Internal Speaker	1x3W (Option)
Indicator	Power Button	1
Power	Power Adapter	120W/19V
Communication	WLAN + BT	802.11 series + BT5.0 (Option)
Peripheral (option)	MSR	3-Track MSR (USB)
	Fingerprint	Fingerprint Reader (USB)
	NFC	NFC Reader (USB)
	2D Scanner	2D Scanner (USB)
	Customer Display	LCM display 2 x 20 characters (USB)
	2nd Display	11.6" 2nd Display
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD
Environment	Operating Temperature	0°C - 35°C (32°F - 95°F)
	Storage Temperature	-20°C-60°C(-4°F-140°F)
	Humidity	20% - 85% RH non-condensing
Dimensions	WxHxD	369 x 264 x 210 mm (14.5" x 10.4" x 8.3")
Mounting	VESA Mount	75x75, 100x100
OS Supported		Windows 10 IoT Enterprise. Linux

